

TYPE 894A PRINTER: AUTOMATIC



Designed for use with Kwik Lok's 872 Automatic Bag Closing Machines. The Type 894A attaches to the 872 Encore, 872 Labelmaster, 872XLS and 872XLS LM machines. The Printer utilizes the Turbo-Print 872 built by Squid Ink Manufacturing, Inc. The printer is a programmable industrial ink jet system.

Not all closures and closure-labels available for the 872 Closers can be used with the 894A. The 872 Labelmaster and 872XLS LM are limited to those closure-labels with the closure glued to the front of the label (reverse lok tracks). Refer to the PRINT AREA SPECIFICATIONS. The Printer can be field installed on 872 Closers.

SPECIFICATIONS

Refer to the specification chart for complete specifications and available options.

APPROXIMATE SHIPPING WEIGHT AND DIMENSIONS

20" x 24" x 38"; 60 lbs.; 10.6 Cu. Ft.
51 cm x 61 cm x 96 cm; 27.2 Kg; 0.3 cu. m

ORDERING INFORMATION

Refer to the specification chart and determine the following:

- A. TYPE:
 1. 894A (Mounted on new closer).
 2. 894AF (Field installed on existing closer).
- B. MODEL:
 1. Select Model A for adapter kit (for fitting to the 872 Closer) with Turbo-Print 872.
 2. Select Model B for adapter kit without Turbo-Print 872 (customers that have existing Turbo-Print 872).
 3. Select Model AH for 200-250 VAC Application.
 4. Select flow direction. (R = Right Hand, and L = Left Hand). Must match hand of closer the printer will be mounted on.
- C. SPECIFY ELECTRICAL REQUIREMENT:
 1. 120 VAC, 1 PH, 60 HZ, 2.08 A
 2. 200-250 VAC, 1 Ph, 50/60 Hz, 1.0 A (Model AH)
- D. SPECIFY CLOSURE:

The closure series must match that of the 872 Closer on which the Printer is to be mounted.
- E. INK MOUNT SYSTEM:
 1. Specify 'horizontal mounts' if the closer is mounted to a flat (deck parallel to 10° of the floor) conveyor.
 2. Specify 'angle mount' if the closer is mounted to a deck angled conveyor (10° to 20°)
- F. Order P18-00154 Encoder wheel for applications that exceed 80 packages/minute.
- G. IN-FIELD INSTALLATION REQUIREMENT:

If mounting the printer to an in-field Closer (versus ordering a new closer with printer), specify the type of reel mast.

 1. Specify 'upright' for reel above the Closer.
 2. Specify 'forward facing' for reel located over the conveyor.

Example Order:

Type 894A, Model AR, 120 VAC, printing on Series J-NRP closures with a horizontal mount ink system.

PRINTING SUPPLIES:

Order from your distributor.

TYPE	MODEL	FLOW DIRECTION	CLOSURES	CLOSURE-LABELS	SPEED
894A	A	R or L	JI, KI, J-NRP, K-NRP, JM-NRP, KM-NRP, VIW, VW-NRP, JW-NRP	CFJ, PF, TF, P-200, T-220 (Medium Duty or Heavy Duty)	REFER TO CLOSER MANUAL
894A	B				
894AF	A				
894AF	B				
894A	AH				
894AF	AH				

TYPE 894A PRINTER: AUTOMATIC

CLOSURE AND CLOSURE-LABEL PRINT AREAS

The printable areas defined here represent the maximum allowable print areas for each style of closure and closure-label. All closure-labels shown on this page are RIGHT HAND.

