

TYPE 894C PRINTER: AUTOMATIC



Designed for use with Kwik Lok's 865 Automatic Bag Closing Machines. The Type 894C attaches to the 865A bag closing machine. The Printer utilizes the Turbo-Print 865 built by Squid Ink Manufacturing, Inc. The printer is a programable industrial ink jet system.

Not all closures available for the 865A Closer can be used with the 894C. Refer to the PRINT AREA SPECIFICATIONS.

The Printer can be field installed on 865A Closures. The closer lok track needs to be shortened prior to mounting the Printer.

The Printer is not intended for use on 865A machines closing horizontally oriented packages.

SPECIFICATIONS

Refer to the specification chart for complete specifications and available options.

APPROXIMATE SHIPPING WEIGHT AND DIMENSIONS

20" x 24" x 38"; 60 lbs.; 10.6 Cu. Ft.
51 cm x 61 cm x 96 cm; 27.2 Kg; 0.3 cu. m

ORDERING INFORMATION

Refer to the specification chart and determine the following:

- A. TYPE:
 1. 894C (Standard) mounted to the 865A painted frame closer.
 2. 894CS Mounted to the 865AS stainless steel frame closer.
- B. MODEL:
 1. Select Model A for adapter kit (for fitting to the 865 Closer) with Turbo-Print 865.
 2. Select Model B for adapter kit without Turbo-Print 865 (customers that have existing Turbo-Print 865).
 3. Select Model AH for 200-250 VAC Application.
 4. Select flow direction. (R = Right Hand, and L = Left Hand). Must match hand of closer the printer will be mounted on.
- C. SPECIFY ELECTRICAL REQUIREMENT:
 1. 120 VAC, 1 PH, 60 HZ, 2.08 A
 2. 200-250 VAC, 1 Ph, 50/60 Hz, 1.0 A (Model AH)
- D. SPECIFY CLOSURE:

The closure-label must match that of the 865A Closer on which the Printer is to be mounted.
- E. Order P18-00154 Encoder wheel for applications that exceed 80 packages/minute.
- F. IN-FIELD INSTALLATION REQUIREMENT:

If mounting the Printer to an in-field closer versus ordering a new closer with Printer), specify the type of reel mast.

 1. Single closure reel mast.
 2. Dual closure reel turret mast.
 3. Single closure reel, low profile mast.
 4. Dual closure reel turret, low profile mast.

Example Order:

Type 894C, Model AR, 120 VAC, printing on Series J-NRP.

PRINTING SUPPLIES:

Order from your distributor.

TYPE	MODEL	FLOW DIRECTION	CLOSURES	CLOSURE-LABELS	SPEED
894C	A	R or L	J-NRP, K-NRP, JM-NRP, KM-NRP, KM57-NRP	CFJ, PF, PFM, TF, TFM P-200, PM-200, T-220, TM-220 (Medium Duty or Heavy Duty Plastic)	REFER TO CLOSER MANUAL
894CS	A				
894C	B				
894CS	B				
894C	AH				
894CS	AH				

TYPE 894C PRINTER: AUTOMATIC

CLOSURE AND CLOSURE-LABEL PRINT AREAS

The printable areas defined here represent the maximum allowable print areas for each style of closure and closure-label. All closure-labels shown on this page are RIGHT HAND.

